

# RUTTER'S ROD SHOP RADIATOR ORDER FORM - SEVEN EASY STEPS

DATE: \_\_\_\_\_ P.O. #:           Seller's Use          

NAME: \_\_\_\_\_

PHONE: \_\_\_\_\_

YEAR & MAKE OF VEHICLE: \_\_\_\_\_

Be advised that by filling out & signing this form you are affirming the accuracy of the information contained herein and authorizing Rutter's Rod Shop to order this custom radiator. Once signed, the purchaser assumes full responsibility for paying for the custom radiator. No refund will be issued unless it can be shown that any errors or defects were the fault of the manufacturer.

\_\_\_\_\_  
Purchaser's Signature

PROPERTY OF RUTTER'S ROD SHOP © - 5277 West NC Hwy 10 - Hickory, North Carolina 28602 - PH: 704 462-1050 - FX: 704 462-0333

1

CIRCLE TOP INLET LOCATION

ENTER TOP INLET DIAMETER

ENTER CORE WIDTH.

ENTER BOTTOM OUTLET DIAMETER.

CIRCLE BOTTOM OUTLET LOCATION.

MARK OUTLET ANGLE.

STRAIGHT

OTHER DESCRIBE \_\_\_\_\_

2

ENTER WIDTH INCLUDING BRACKETS

ENTER MOUNTING BRACKET WIDTH.

ENTER WIDTH WITHOUT BRACKETS.

3

CIRCLE ONE.

MOTOR SIDE

4

ENTER TOP TANK OVERHANG WIDTH.

MOTOR SIDE

CHECK THIS BOX IF NONE.

5

CIRCLE ONE.

CONVENTIONAL      REAR FILL

6

ENTER SIDE WIDTH.

ENTER DISTANCE BETWEEN TOP OF TANK AND TOP OF MOUNTING BRACKET.

ENTER MOUNTING BRACKET LENGTH.

ENTER DISTANCE BETWEEN BOTTOM OF MOUNTING BRACKET AND BOTTOM TANK.

ENTER TOTAL RADIATOR HEIGHT.

7

SIDE VIEW

NOTE: ALL SIDES HAVE KEY HOLES, MOVEABLE BRACKETS, & CARRIAGE BOLTS FOR FASTENING

KEY HOLES WILL BE PLACED ACCORDING TO YOUR DESIRED BRACKET LOCATION.

CHOOSE MOUNTING BRACKET PLACEMENT.

ENGINE SIDE      CENTER      GRILL SIDE      SKEWED      SKEWED

A      B      C      D      E